







AGM VRLA SOLAR BATTERY

FEATURES

-  Non-Spillable Sealed Maintenance free VRLA battery with Absorptive Glass Mat Technology
-  Excellent Cyclic Service Life & Low Self-Discharge
-  Superior High Temperature Corrosion Resistant Alloy
-  Enhanced Active Surface Area for Excellent Charge Acceptance
-  Superior Charge Retention & Recovery from Deep Discharge
-  Specially Suited For High Temperature Partial State of Charge (PSoC) Operation.



SPECIFICATIONS

SOLAR NXT (12V)

Model	Nominal Voltage (V)	Capacity @C20 at 25°C (Ah)	Battery Weight (kg) ±5%	Battery Dimensions		
				Length ±3 mm	Width ±3 mm	Height ±3 mm
SOLARNXT26	12	26	10	178	124	179
SOLARNXT42	12	42	15	200	165	170
SOLARNXT65	12	65	22	350	166	174
SOLARNXT100	12	100	35	407	173	235
SOLARNXT120	12	120	40	452	172	239
SOLARNXT150	12	150	48	557	172	240
SOLARNXT200	12	200	67	533	250	240

SOLAR NXT (2V)

Model	Nominal Voltage (V)	Capacity @C10 at 25°C (Ah)	Module Dimensions			
			Length ±3 mm	Width ±3 mm	Height ±3 mm	Weight (kg) ±5%
SOLARNXT340	2	340	635	545	385	269
SOLARNXT400	2	400	862	586	297	228
SOLARNXT600	2	600	841	552	370	312
SOLARNXT1000	2	1000	1004	640	580	265